



H5 audits vision: Network Flows visibility technology.

H5 audits R&D team has designed innovative technologies that enable enterprises, service providers and governments to enhance their global network and application visibility. With H5 Appliance, corporations can deploy an “easy to use” and comprehensive software and hardware solution that allows the various teams to access IT information in an adapted format (in regards to their position and expertise). Using a common tool for IT Reporting allows to broadcast a clear and comprehensive information on applications behavior and trending of the network. H5-Appliance provides a powerful network visibility solution for **Network operations center** to pilot the IT, for **Network managers** who are responsible for building and planning growth & IT changes and for **the Helpdesk** interfacing and supporting users with IT issues on daily basis.

Cyclic capture : Embedded rolling buffer

The H5-200cc Appliance has additional resources storage 100% dedicated to Network traces storage and history. This new feature allows to drill-down on a specific traffic, or a selected IP or a monitored object to get the associated network trace on a past period; it can be easily exported in a pcap file format. Embedded rolling-buffer is available from 4.0 version. Please contact your sales department for upgrading older versions.

Part Number	H5-200	H5-200cc
Form Factor	1U Rack: 43mm x 426 mm x 356	1U Rack: 43mm x 426 mm x 356
Acquisition interfaces	Copper 2x10/100/1000	Copper 2x10/100/1000
Management interfaces	Copper 1x10/100/1000	Copper 1x10/100/1000
Remote Access interface	Yes (IPMI)	Yes (IPMI)
Total Throughput pps (1)	50 000 pps (300 Mbit/s)	50 000 pps (300 Mbit/s)
Storage Capacity for Statistics	250 GB	250 GB
1 min / 5 min / 1 hour / 1-day Data storage	30 days / 3 month / 6 months/ 1 year	30 days / 3 month / 6 months/ 1 year
Storage Capacity for H5 cap module	NA	2 TB
Monitored objects	200	200
Business Flows	100	100
VLAN	100	100
Weight	9 Kg	10 Kg
Operating Temperature	0°C à +50°C / +32°F to +122°F	0°C à +50°C / +32°F to +122°F
Power Supply	1 x 260W	1 x 260W
Redundant	No	No
Voltage	100-240 Volts	100-240 Volts

(1) Based on average packet size of 750 bytes, $\rightarrow (50\,000 \times 750 \times 8) / (1\,000\,000\,000) = 0,3$



Contact us
Tel : +33 1.56.83.77.36.
commercial@h5audits.com

Join us
www.h5audits.com